



SCREEN CHEMICALS

THINNERS

(For flat and rotary screen making)

Technical Data Sheet N° 11/SC-F

1st June 2006

ENGRAVING

Solvent thinners for lacquers and adhesives; use and characteristics suitable for the different products. All thinners are formulated without 2-etoxy-ethyl-acetate.

For directions for use and necessary quantities, see the single technical data sheets of the products.

Thinners are added slowly to the products, mixing until completely absorbed.

DILUENTE 504 EXTRA

code 152504

Used generally under normal temperature and work conditions with DURAL ARCHIM protection lacquers, retouching lacquers ROTORET and LACCA MRF.

DILUENTE 501

code 151501

Thinner for the polyurethane adhesives TENAX HT and COLTEX R, when working with a very fine mesh.

PACKINGS

1 and 5 lt.

Store in tightly closed containers, protected against heat and sources of ignition.

Mix thoroughly before use.

Information contained in this Technical Data Sheet constitute the result of tests carefully carried out and express our best as well as most up-dated know-how. Nevertheless these news are published only as information and can't neither engage the responsibility of our company nor provide a whatsoever pretext for disputes of any kind, which could any how be connected to the usage of above described products. In consideration of the above the usage conditions are not under our control.

KIIAN S.p.A. – Via A. De Gasperi, 1 – 22070 LUISAGO (CO)
Tel: + 39 031 9090111 – Fax: +39 031 920505 e-mail: info@kiaan.it